



# Filter Clean

*For D.E., Cartridge,  
& Sand Filters*

**KEEP OUT OF REACH OF CHILDREN**  
**WARNING: CORROSIVE TO EYES & SKIN -**  
**HARMFUL IF SWALLOWED.**

See additional precautions and first aid on back panel.

**Powerful Cleaner & Degreaser**

**Removes Oils, Grease, & Filter  
Clogging Debris**

**Increases Filter Efficiency & Filter Life**

**NET CONTENTS**  
**32 FL. OZ (946 ml)**

This liquid filter cleaner greatly improves filter life and efficiency. It is specially made to cleanse suntan oil, and grease as well as scale and mineral deposits from pool and spa filters of all types: cartridge, sand, and D.E. Regular use of this product will assure proper filtration.

#### **DIRECTIONS FOR USE**

When preparing or using this product, take care not to splash, drip, or use on surfaces such as ceramic tile, linoleum, formica brand counter surfaces, carpeting, etc. as etching or discoloration of these surfaces may take place. This product is intended only for use as a pool filter cleaner.

**SAND FILTERS:** Turn off inlets and outlets for all chemical feeders. Close main drain and place filter in backwash position. Slowly add one quart Filter Cleaner through skimmer while backwashing. Filter Cleaner can also be added through the sand fill port. Run filter until product begins to come out of the backwash water or until the product is seen through a filter viewing cell. Soak filter for 8-10 hours. After soaking, backwash filter until water comes out clean and foam clears. Reverse procedure and start normal filter operation. For sand filters containing more than 300 pounds of sand, add two quarts Filter Cleaner.

**CARTRIDGE FILTERS:** Stop filter operation. Bleed off excess pressure through the filter safety valve. Open filter unit, remove cartridge from filter, and rinse excess loose dirt with a water hose from top to bottom. Place cartridge into a container of appropriate size and add 1 quart Filter Cleaner and 5 gallons water. Make sure filter unit is completely covered by the cleaner. Soak 8-10 hours. After soaking, rinse with hose at maximum pressure to remove excess Filter Cleaner or until foam residue is completely washed off. Re-install cartridge, and resume normal filter operation.

**DIATOMACEOUS EARTH FILTERS:** Stop filter operation. Bleed off excess pressure through safety valve. Remove filter elements (grids) from filter and rinse off excess dirt with a hose from top to bottom. Place grids in a bucket and add 1 quart Filter Cleaner and 5 gallons water. Make sure grids are fully immersed in cleaner. Soak 8-10 hours. After soaking, rinse out excess filter cleaner with hose at maximum pressure. Re-install grid and add new filter media. Resume normal filter operation.

#### **WARNING** **KEEP OUT OF REACH OF CHILDREN**

This product contains sodium hydroxide. Irritant to eyes and mucous membranes. Avoid contact with skin, eyes or clothing. Harmful if swallowed. Do not inhale or swallow. Do not mix with chlorine-type bleaches or other household chemicals.

#### **FIRST AID**

**EYE CONTACT:** Flush thoroughly with plenty of water for at least 15 minutes. Get prompt medical attention.

**IF SWALLOWED: DO NOT INDUCE VOMITING.** If conscious, give 1 to 2 glasses of water and call a physician immediately. Never give anything by mouth to an unconscious victim.

**SKIN CONTACT:** Flush area with plenty of water, then with soap and water. If irritation persists, get medical attention. Remove and wash clothing before reuse.

Distributed by:  
**Blue Wave Products**  
St. Charles, Illinois  
60174  
1-800-759-0977

REV 123108

32 oz.  
30 oz.  
28 oz.  
26 oz.  
24 oz.  
22 oz.  
20 oz.  
18 oz.  
16 oz.  
14 oz.  
12 oz.  
10 oz.  
8 oz.  
6 oz.  
4 oz.  
2 oz.