



Super Rust & Scale

*Powerful Scale & Stain
Preventer!*

KEEP OUT OF REACH OF CHILDREN

DANGER: EYE & SKIN IRRITANT.

See additional precautions and first aid on back panel.

**Prevents Ugly Stains,
Scaling & Brown Water**

Lightens Some Existing Stains

Perfect for Well Water

**NET CONTENTS
16 FL. OZ (473 ml)**

DIRECTIONS FOR USE

Super Rust & Scale is best used for metallic stain removal and prevention of hard water scaling. It sequesters (picks up) the material causing stains and scale and holds them in solution. If stains persist, they may be old ones requiring complete cleaning of the walls, or stains of an organic nature. Dissolved metals and minerals (such as Iron, Calcium, Manganese, and Magnesium) in pool water and corrosion of metal pool fittings will often cause staining and/or scaling. Do not let pH of pool water fall below 7.0 or serious corrosion problems may result. For scale prevention it is also essential to maintain pH at 7.2 to 7.6, total alkalinity at 100 to 150 ppm, and calcium hardness at 100 to 275 ppm.

STAIN REMOVAL

1. Before using Super Rust & Scale, adjust pH between 7.2 and 7.6.
2. For best results, use Super Rust & Scale in the evening with pool pump and filter operating overnight.
3. Add 16 ounces (1/2 bottle) per 10,000 gallons by premixing into plastic pail of water first. Dispense solution at deep end of pool.
4. Cloudiness may develop with the appearance of white flakes. This is normal indicating Super Rust & Scale is working and cloudiness will eventually disappear.

STAIN AND SCALE PREVENTIVE MAINTENANCE

1. Follow all steps outlined above for STAIN REMOVAL.
2. Repeat application of 2 ounces per 10,000 gallons every 4 to 5 days.

HARD WATER NOTE: In areas with hard water where calcium harness exceeds 300 ppm, it is advisable to double the dosages listed above. However, DO NOT increase the dosages more than double for one application.

WINTERIZING

Before applying, start with a clean, properly balanced pool. Add one pint of this product, pouring it around the perimeter of the pool. Wait 2 hours before adding additional winterizing chemicals.

PRECAUTIONARY STATEMENTS

DANGER. CORROSIVE TO EYES AND SKIN. Causes eye irritation. Avoid contact with eyes or skin. Wear rubber gloves and safety glasses or goggles when handling. Not for internal use.

FIRST AID

IF CONTACT WITH EYES OCCURS: Immediately flush with cold water for at least 15 minutes. Then get immediate medical attention.

IF CONTACT WITH SKIN: Wash exposed area with plenty of soap and water. Remove contaminated clothing and wash. If irritation persists, get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, have trained person administer oxygen. If not breathing, give artificial respiration. Call a physician immediately.

IF SWALLOWED: DO NOT INDUCE VOMITING. Rinse with water or milk. Slowly drink 1 to 2 glasses of milk or water. Never give anything by mouth to an unconscious person.

NOTICE: Manufacturer and seller's guarantee shall be limited to the terms of this label. Neither shall be held responsible for any personal injury, or property damage, or other loss resulting from the handling, storage, and use of this product not in strict accordance with the directions on this label.

Distributed by:
Blue Wave Products
St. Charles, Illinois
60174
1-800-759-0977

REV060512

16oz. __
15oz. __
14oz. __
13oz. __
12oz. __
11oz. __
10oz. __
9oz. __
8oz. __
7oz. __
6oz. __
5oz. __
4oz. __
3oz. __
2oz. __